NetCamera

A03-IPCAM-W54

IP Security Wireless Camera

- Monitoring Locale e Remoto
- Interfaccia IP Lan/WLan
- Wireless IEEE802.11g con supporto WEP/WPA-PSK
- Software di gestione incluso (IPView SE)
- Supporta sia i controlli ActiveX che Java applet
- Modalità cattura immagini e registrazione video
- Rilevamento del movimento via software
- Facile installazione e gestione

NetCamera rappresenta la soluzione perfetta per inviare video, per la videosorveglianza remota o la trasmissione di immagini in tempo reale su Internet o Intranet. E' dotata di una potente CPU che la rende un sistema autonomo; può essere collegata, tramite il cavo di rete, direttamente alla LAN o utilizzare l'interfaccia wireless in standard IEEE802.11g utilizzando i più evoluti protocolli di sicurezza. Completa la dotazione uno zoom hardware 4X digitale (per avere dettaglio nei primi piani). NetCamera può essere gestita e controllata anche da remoto, in maniera semplice ed intuitiva, tramite un PC o portatile collegato in Internet (o Intranet) utilizzando un qualsiasi browser web in qualunque momento e luogo.

IPCam

NetCamera

NetCamera
IP Security Wireless Camera

CARATTERISTICHE TECNICHE

Video specification
Resolution: 640 x 480 pixel
Sensor:color CMOS sensor
Gain control: Automatic
Exposure: Automatic
White Balance: Automatic
Focal Length: 6.0 mm
Aperture: F=1.8
Focus Extent: 20 cm - ∞
Lens mounting: Fixed board lens

Image (Video Setting)
Image compression: JPEG
Frame rate: QCIF@30fps,25fps@CIF, 10fps@VGA
Compression Rate selection: 5 levels, very low, low, middle, high, very high
Frame rate setting: 1, 5, 7, 15, 20, auto (depends on the video format)
Video resolution: 160x120, 320x240, 640x480
Brightness control: Range 1-128
Contrast control: Range 1- 128
Saturation Control
Digital Zoom: (4X)
Upside down and Mirror

Hardware Interface
LAN Connector: One RJ-45 port to connect to 10/100Mbps Ethernet, auto-sensed
Wireless LAN: Built-in 802.11g (Wi-Fi compliant) wireless LAN module
LED Indicator: Power LED (Blue), Link LED (Orange)
Power Supply: DC 5V, switching type
Power Communication: 5 Watt (1000mA x 5V)
Antenna Connector: 1 connectors (Reverse-SMA)

Communication Support
Communication: 10/100Mbps Ethernet and 802.11g wireless LAN.
Encryption: WAP-PSK, WEP 128 bit, WEP 64 bit or OFF
Communication protocol: HTTP, FTP, TCP/IP, UDP, ARP, ICMP, BOOTP, DHCP, PPPoE

System
CPU: RDC R2880
RAM: 8M Byte
Flash ROM: 2M Byte
OS: RTOS
Browser Support

System requirement
CPU: Pentium III, 700 MHz or above
Memory Size: 64 MB (128 MB recommended)
VGA card resolution: 800x600 or above
Internet Explorer 5.0 or above (ActiveX Mode –View Image supports Internet Explorer under Windows OS)
Netscape 6.0 or above

IPView SE Application
Support OS: Win 98 SE, Win 2000, Win Me, Win XP
System requirement for IPView:
CPU: Pentium III, 700 MHz or above
Memory Size: 128 MB (256 MB recommended)
VGA card resolution: 800x600 or above
Powerful application software for image capture and video recording
- Multiple Video Window Simultaneously
- Motion Detection with alert and E-mail sending.
- Recording triggered by Motion Detection, Schedule, and Manual.
- Single Frame Image Snap shot

Operating environment
Operating temperature: 5°C ~ 40°C
Storage temperature: -25°C ~ 50°C
Humidity: 5% ~ 95% non-condensing

Package Contents
One IP Security Wireless Camera
One Quick Installation Guide
One External Antenna (2.2 dBi)
One Installation CDRom with IPView SE
One Camera Stand
One DC Power Adapter
One RJ-45 Ethernet Cable

PRODOTTO:	NetCamera
CODICE:	A02-IPCAM-W54
CODICE EAN:	8026974009537

Atlantis Land S.p.A. - Viale De Gasperi 122
20017 Mazzo di Rho - Milano - ITALY
Phone: +39 - (0)2 - 93.90.60.85 Fax: +39 - (0)2 - 93.90.61.61
Web: www.atlantis-land.com
E-Mail: info@atlantis-land.com

NetCamera

I dati possono essere cambiati senza preavviso

A02-IPCAM2-W54_SI_065

IPCam